




SPECIFICATIONS

HangerMate® Threaded Rod Anchoring System EZH155 Anchors



Features & Benefits

- Cross- drilled and tapped for attaching 1/4-20 threaded components to steel
- Solid, one piece cold formed part; head cannot spin off or unscrew from body
- #3 self-drilling point for steel thicknesses of .060 – .250"

Performance Values for EZG155 Anchor

Steel Thickness	Average Ultimate Value (lbs)
0.062"	1739
0.074"	1944
0.104"	2420
0.111"	2570
0.189"	2809
0.248"	2809

1. The loads indicated above are average ultimate values achieved under laboratory conditions and appropriate safety factors should be applied for design purposes.
2. NFPA (National Fire Protection Assoc.) minimum fastening requirements are five times the weight of a 15 ft section of water-filled pipe plus 250 lbs. This is 1475 lbs. for 4" pipe.
3. All test values were obtained using 3/8-16 rod. When 1/4-20 rod is used, the strength of the rod may be less than the pull-out values of the anchors.
4. Loads were determined by testing products in the orientation for which they were designed to be used. End-drilled parts were pulled in line with the anchor's axis while cross-drilled parts were tested with the force perpendicular to the axis.

EZH155 HangerMate® Anchors

Application Material:
Steel .060" – .250"

Specification:
1/4" shank diameter, one-piece anchor with cross-drilled head to accept 1/4-20 threaded rod and components, #3 self-drilling point and self-tapping threads

FM Approvals and UL Listings:
None; 1/4-20 rod not used for sprinkler applications

Head Style:
9/16" diameter head cross-drilled and tapped to accept 1/4-20 threaded components

Head Height
3/4"

Drive Hex Size:
1/2" across flats

Shank Length:
1"

Shank Threads:
1/4-20 self-tapping

Point Type:
#3 self-drilling

Material & Heat Treat:
Carbon steel (AISI C10B21) case hardened and tempered

Finish:
Zinc plated per ASTM B633 Type II Class 5

Installation Tools:
HangerMate® drive socket: EZE215 with safety set feature; automatically disengages when anchor is seated

Recommended power tool: Contractor-grade screw gun; 12 volt min. cordless or 4.5 amp min. corded tool 1300 – 2000 rpm

For more information, contact
Elco Construction Products • 1.800.435.7213
www.elcoconstruction.com